

RUSHMOOR BOROUGH COUNCIL

STREET NAMEPLATE SPECIFICATION

Street nameplate unit ready for installation shall comprise:

PLATES

5mm thick aluminium backed polycarbonate coloured white with black border 12.5mm wide. Plate corners to be rounded to a radius of 25mm. Black Kindersley lettering 90mm high formed in PVC

POSTS AND BACKBOARDS

Formed in black recycled plastic. Posts 75mm square by 1200mm long, drilled for metal pin 150mm from base of post. Backboards 30mm thick by 150mm wide, of length and number to suit the plate(s) being attached. 2 metal pins to be supplied with each complete nameplate.

CONSTRUCTION

Backboards to be attached to posts with coach bolts, which also pass through the nameplate. Nameplates to be additionally secured to backboards with vandal-proof fixings at maximum spacing of 225mm.

ERECTION

150mm metal pin to be inserted through each post 150mm above base. Posts to be set in ground approximately 450mm, as necessary to make centre of nameboard nominal 600mm above ground level, with sign fixed horizontally. Base of each post to be secured with 2 heaped shovels of 6:1 concrete mix. Remainder of hole to be backfilled and ground reinstated as appropriate for location.

CUL-DE-SAC PLATE

To be added to right hand end of street nameplate (with suitable extra length backboard) when required.

Height to top of assembly to be 1350mm above ground level.

Depth of foundations 950mm.

As supplied by
Signway Supplies Ltd
Signway House
Kingsland Business Park
Stroudley Road
Basingstoke RG24 8UG

Tel: 01256 811234



RUSHMOOR
BOROUGH COUNCIL